


Product: Velis Armchair

STRUCTURE / BACKREST


Wood



Beige aniline stained
Ash wood




Biscuit stained
Ash wood




Moka stained
Ash wood



Wengé stained
Ash wood




Carbon stained
Ash wood



Dark grey stained
Ash wood

STRUCTURE / BACKREST

Wood



Matt Canaletto walnut

COVER

Fabric: Ado | Cat. 1



Bianco \ C5A




Panna \ C5B




Beige \ C5C



Grigio Chiaro \ C5G



Nocciola \ C5D



Marrone \ C5E

Ado | Cat. 1

Composition:

39% VI, 25% PES, 17% LI,
14% CO, 4% AC, 1% AF

Martindale:

20.000 rubs

Pilling:

2/3

Maintenance:




Fabric: Ares | Cat. 1



Bianco \ C7A



Ghiaccio \ C7B




Oliva \ C7C



Marrone \ C7D



Nero \ C7E



Senape \ C7F

Ares | Cat. 1

Composition:

77% PL, 17% CO,
6% PC

Martindale:

50.000 rubs

Pilling: 4/5

Maintenance:



COVER

Fabric: Aida | Cat. 1




Bianco \ A2D




Beige \ A2E



Sabbia \ A2F




Pepe \ A2G




Grigio \ A2H




Antracite \ A2I



Tronco \ A2J



Rubino \ A2K



Petrolio \ A2L

Aida | Cat. 1

Composition:

68% PL, 32% PP

Martindale:

135.000 rubs

Pilling:

4/5

Fire tests:

1IM-UNI 9175 - Classe 1-UNI

9177 - EN 1021 Part 1/2 -

DIN 4102-B1 - NF D-60

013-A18 - CAL TB 117:2013 -

IMO MED-FTP 307 Part 8 -

Önorm B 3825

Notes:

IMO-MED - Sound absorbent

- Proposition 65

Maintenance:




COVER


Fabric: Arte | Cat. 1




Bianco \ A1D




Rosa \ A1E



Grigio chiaro \ A1F




Verde mattone \ A1G




Pepe \ A1H



Beige \ A1J



Blu oltremare \ A1K



Blu arancio \ A1L

Arte | Cat. 1

Composition:

68% PC, 16% PL,
16% CO

Martindale:

25.000 rubs

Pilling: 3/4

Maintenance:




Cleaning:

Use a vacuum cleaner with soft brushes. If stained, immediately act on the stain by dabbing it with a clean cloth to prevent it from spreading. Professional washing is recommended.

COVER


Fabric: Barrique | Cat. 2




Panna \ A7D



Beige \ A7E




Petrolio \ A7F



Sabbia \ A7G




Grigio \ A7H



Terracotta \ A7I



Rubino \ A7J



Antracite \ A7K



Grigio scuro \ A7L

Barrique | Cat. 2

Composition:

33% CO, 15% VI,
12% LI, 20% PA, 20% PL

Martindale:

100.000 rubs

Pilling: 3/4

Fire tests:

BS 5852 Cigarette -BS
5852 Match - CAL TB
117:2013

Maintenance:



Fabric: Bliss | Cat. 2



Bianco \ H1X



Beige \ H1Z



Panna \ H1Y



Nocciola \ H1W

Bliss | Cat. 2

Composition:

67% VI, 33% LI

Martindale: 20.000 rubs

Pilling: 4

Test standard:

BS 5852:1979 Part 0,
Part 1

Maintenance:



COVER


Fabric: Boss | Cat. 2



Bianco \ C7N




Panna \ C7J



Rosa \ C7G



Grano \ C7P




Tortora \ C7L



Oliva \ C7M



Antracite \ C7H



Celeste \ C7K



Grigio \ C7I

Boss | Cat. 2

Composition:

58% CO, 37% VI, 5% PL

Martindale:

25.000 rubs


Pilling: 4/5

Maintenance:



COVER

Fabric: Brera (velvet) | Cat. 2



Bianco \ A4D



Beige \ A4E




Tronco \ A4F



Salvia \ A4G



Antracite \ A4H



Lilla \ A4I



Tortora scuro \ A4K

Brera | Cat. 2

Composition:

100% CO

Martindale:

40.000 rubs

Pilling: 3/4

Fire tests:

BS 5852 Cigarette -BS

5852 Match - CAL TB


117:2013

Maintenance:




COVER


Fabric: Bridge (velvet) | Cat. 2



Bianco \ A3D



Panna \ A3E




Grigio \ A3F




Antracite \ A3G



Salvia \ A3H



Mattone \ A3I



Prugna \ A3J



Blu oltremare \ A3K



Nero \ A3L

Bridge | Cat. 2

Composition:

100% TREVIRA® CS

Martindale:

100.000 rubs

Pilling: 5

Fire tests:

UNI 9175 1IM - UNI 9177

Classe 1 - EN 1021-2 - BS

5852 Crib 5 - DIN 4102 -

B1 - NF92.503 - M1

Note:

Sound absorbent

Maintenance:



Cleaning:

Use a vacuum cleaner with soft brushes. If stained, immediately act on the stain by dabbing it with a clean cloth to prevent it from spreading. Professional washing is recommended.

COVER

Fabric: Calipso | Cat. 3




Panna \ A8A




Sabbia \ A8B



Tortora \ A8C



Antracite \ A8D



Nero \ A8E

Calipso | Cat. 3

Composition:

35% CO, 25% PC, 18% PL, 13% VI, 9% WO

Martindale:

40.000 rubs

Pilling: 5

Fire tests:

BS 5852 Cigarette - BS

5852 Match - CAL TB

117:2013 - EN 1021-1/2

Maintenance:




Fabric: Calla | Cat. 3




Panna \ A8L




Sabbia \ A8M




Smeraldo \ A8N



Celeste \ A8P



Pepe \ A8Q



Rubino \ A8R

Calla | Cat. 3

Composition:

5% CO, 25% VI, 13% LI, 15% WO, 25% PL, 15% PC, 2% PA

Martindale:

45.000 rubs

Pilling: 4

Fire tests:

BS 5852 Cigarette - BS

5852 Match - CAL TB


117:2013

Maintenance:



COVER

Fabric: Cielo | Cat. 3




Panna \ A6H



Blu oltremare \ A6I



Sabbia \ A6K



Tronco \ A6J



Mattone \ A6L

Cielo | Cat. 3

Composition:

47% CO, 18% LI,
35% VI

Martindale:

50.000 rubs

Pilling: 3/4

Fire tests:

BS 5852 Cigarette - BS
5852 Match - CAL TB
117:2013


Maintenance:




Fabric: Core | Cat. 3




Ghiaccio \ E1T




Paglia \ E1W




Senape \ E1Y




Marrone Chiaro \
E1Z



Talpa \ E1V



Testa di Moro \
E1X



Fieno \ E1U

Core | Cat. 3

Composition:

59% PL, 25% PC,
16% CO

Martindale:

30.000 rubs

Pilling: 3/4

Maintenance:



COVER


Fabric: Cortina | Cat. 3



Bosco \ A9A




Salvia \ A9B



Blu oltremare \ A9C




Avio \ A9D




Beige \ A9E




Grigio \ A9F




Antracite \ A9G



Senape \ A9H



Terracotta \ A9I



Mattone \ A9J

Cortina | Cat. 3

Composition:

100% PES FR

Martindale:

50.000 rubs

Pilling: 4/5

Fire tests:

BS 5852 Cigarette - BS 5852 Match
- EN 1021-1/2 - BS7176 Low hazard
- CAL TB117:2013 - NFPA 260 -
IMO Annex 1 Part 8 - UNI 9175 1IM
- NF D 60 013 - DIN 4102 B2

Notes:

STANDARD 100 by OEKO-TEX® -
REACH approved chemicals and
dyes - Biocide and PFCs free -
Zero-waste production - Acoustic
certificate: EN ISO 354

Maintenance:



Cleaning:

Use a vacuum cleaner with soft brushes. If stained, immediately act on the stain by dabbing it with a clean cloth to prevent it from spreading. Professional washing is recommended.

COVER

Fabric: Dafne | Cat. 4



Bianco \ B2A




Panna \ B2B



Sabbia \ B2C



Mattone \ B2D



Blu oltremare \ B2E



Grigio \ B2F



Antracite \ B2G



Rubino \ B2H

Dafne | Cat. 4

Composition:

100% TREVIRA® CS

Martindale:

170.000 rubs

Pilling: 4

Fire tests:

Classe 1-IM - BS 5852

Cigarette - BS 5852


Match - CAL TB

117:2013


Maintenance:




Fabric: Delta | Cat. 4




Panna melange \ B1C



Tronco melange \ B1D



Antracite melange \ B1E



Blu mattone \ B1F

Delta | Cat. 4

Composition:

50% CO, 33% VI, 17% LI

Martindale:

35.000 rubs

Pilling: 3/4

Fire tests:

BS 5852 Cigarette - BS

5852 Match - CAL TB


117:2013

Maintenance:




COVER


Fabric: Dalí | Cat. 4



Bianco \ C6U




Sabbia \ C6V




Fango \ C6Q




Grigio \ C6K




Antracite \ C6L




Pepe \ C6M



Blu Navy \ C6S




Grigio Chiaro \ C6I




Arancione \ C6T



Senape \ C6H



Rubino \ C6P



Salvia \ C6N

Dalí | Cat. 4

Composition:

95% WV, 5% PA

Martindale:

100.000 rubs

Pilling: ≥ 4/5

Fire tests:

CAL TB 117:2013 - EN

1021-1/2 - UNI 9175 1IM -

ÖNORM B1-Q1 - IMO

2014/90/EU Marine

Equipment Directive (MED)

Notes:

Sound absorbent - Natural,
renewable material -

RAL-UZ 117 attachment

2+3 - IWTO guidelines for

wool sheep welfare -

FR-Free - AB 2998 (US

Export Standard) - REACH

(EU Export Standard) -

Naturally stain resistant

Maintenance:




COVER


Fabric: Dolino (linen) | Cat. 4



Sabbia \ C8D



Antracite \ C8F



Grigio \ C8K




Senape \ C8M



Verde oliva \ C8P




Denim \ C8S




Blu scuro \ C8Y




Celeste \ S2C



Rosso \ C9G



Arancione \ C9M



Tortora \ C9U



Grigio scuro \ C9V

Dolino | Cat. 4

Composition:

100% LI

Martindale:

>25.000 rubs

Pilling: 4/5

Test standard:

BS 5852:1979 Part 0,
Part 1

Maintenance:



COVER

Fabric: Doro (velvet) | Cat. 4



Crema \ H2H



Nocciola \ H2J




Notte \ H2N



Sabbia \ H3C



Argilla \ H3D




Ocra \ H3E



Ruggine \ H3F



Rosso imperiale \ H3G



Lilla \ H3H




Prugna \ H3I



Grigio \ H3J




Celeste \ H3A



Salvia \ H3L



Bosco \ H3M



Nero \ H3B

Cleaning:

Use a vacuum cleaner with soft brushes. If stained, immediately act on the stain by dabbing it with a clean cloth to prevent it from spreading. Professional washing is recommended.

Doro | Cat. 4

Composition:

100% CO

Martindale:


100.000 rubs

Maintenance:




COVER


Eco-Leather: Flamingo B | Cat. 2




Ecru \ Q1C




Beige \ Q1D



Grigio Scuro \ Q1E




Tortora Scuro \
Q1A




Nocciola \ Q1F




Bordeaux \ Q1H



Blu Notte \ Q1I



Nero \ Q1B



Mogano \ Q1G

Cleaning:

Ordinary dirt and soluble stains can be removed by using a soft sponge with neutral soapy water. Dab the stain and clean with a soft cloth and water. Gently rub the surface with a cloth dampened in ethyl alcohol to remove more stubborn stains.

Flamingo | Cat. 2

Composition:

10% CO, 20% PES,
0,1% PU, 69% PVC

Martindale:

102.400 rubs

Fire tests:

UNI 9175 1IM -
IMO-FTP - CAL TB
117:2013

Maintenance:



COVER

Eco-Leather: Falabella | Cat. 3




Panna \ KN



Beige \ KP



Tortora chiaro \
PM



Grigio chiaro \ PF



Antracite \ PG



Verde oliva \ YA



Bronzo \ KV



Marrone testa di
moro \ KU

Falabella | Cat. 3

Composition:

47,5% PU, 31,5 CO,
21% PL

Martindale:

>200.000 rubs

Fire tests:

UNI 9175 1IM -EN
1021-1/2 - BS 5852
Crib 5 - BS 5852
Match - IMO 2010
FTP CODE - CAL
TB 117:2013

Notes:

Waterproof -
Resistance to mould
and bacteria -
Phthalates free

Maintenance:



Cleaning:

Ordinary dirt and soluble stains can be removed by using a soft sponge with neutral soapy water. Dab the stain and clean with a soft cloth and water. Gently rub the surface with a cloth dampened in ethyl alcohol to remove more stubborn stains.

COVER

Leather: Geo | Cat. A



Panna \ P2A



Grano \ P1B



Beige scuro \ P1D



Tortora \ P2D



Ruggine \ P2C



Nocciola \ P1K



Tronco \ P1M




Grigio scuro \ P2G



Noce \ P1N



Marrone scuro \
P2H



Terracotta \ P1T



Rosso \ P1V



Bordeaux \ P1W



Melanzana \ P2N



Celeste \ P2Q



Blu cadetto \ P2S

COVER

Leather: Geo | Cat. A



Blu prussia \ P2T



Verde chiaro \ P3B



Verde \ P3C



Nero \ P2F

Geo | Cat. A

Raw hide:

European bovine

Surface:

Corrected grain

Thickness:

0,9-1,1 mm

Dry friction:

ISO 11640 > 1,000 cycles

Fire tests:

EN 1021-1/2 - BS 5852

Cigarette - BS 5852 Match -

IMO MED FTP8 A652 - CAL

TB 117:2013

Maintenance:




Characteristics and cleaning:


As guarantee of the quality and authenticity of our products, we advice that porosity, scars, grain differences on the surface of the leather coverings, are not to be considered defect, but characteristics of the animal's life. To clean use a cloth dampened in warm water and properly squeezed. Any stains should be removed promptly with an absorbent cloth. Do not rub.

COVER


Leather: Galea | Cat. B




Bianco \ C4I




Beige \ C4Q




Tortora chiaro \ C4T




Tortora \ C4U




Zucca \ C4P



Rosso scuro \ C4H




Dattero \ C4V




Castagna \ C4K




Marrone scuro \ C4L



Marmotta \ C4S



Verde muschio \ C4W




Verde mimetico \ C4N




Grigio \ C4R



Grigio chiaro \ C4J



Bluette \ C4G



Blu \ C4M



Nero \ C4F

Galea | Cat. B

Raw hide:

European bovine

Surface:

Smooth grain

Thickness:

1,0 - 1,2 mm

Dry friction:

ISO 11640 > 1,000 cycles

Fire tests:

EN 1021-1/2 - BS 5852

Cigarette - BS 5852 Match -

IMO MED FTP8 A652 - CAL

TB 117:2013

Maintenance:



Characteristics and cleaning:

As guarantee of the quality and authenticity of our products, we advice that porosity, scars, grain differences on the surface of the leather coverings, are not to be considered defect, but characteristics of the animal's life. To clean use a cloth dampened in warm water and properly squeezed. Any stains should be removed promptly with an absorbent cloth. Do not rub.

COVER


Leather: Nina | Cat. B



Naturale \ KK



Nocciola \ XZ



Marrone \ KL



Nero \ KJ

Nina | Cat. B

Raw hide:
European bovine
Surface:
Full grain
Thickness:
1,0 - 1,2 mm
Dry friction:
I.U.F.450 > 3

Characteristics and cleaning:

As guarantee of the quality and authenticity of our products, we advice that porosity, scars, grain differences on the surface of the leather coverings, are not to be considered defect, but characteristics of the animal's life. To clean use a dry cloth. Any stains should be removed promptly with an absorbent cloth. Do not rub.

COVER

Leather: Nabuk | Cat. C



Nocciola \ E2Q



Tortora \ E2T



Avena \ E2R



Marmotta \ E2U



Wengè \ E2S



Blu \ E2V

Nabuk | Cat. C

Raw hide:

European bovine

Surface:

Water-repellent Nabuk
3M scotchgard

Thickness:

1,1 - 1,3 mm

Dry friction:

ISO 11640 > 100 cycles

Fire tests:

EN 1021-1/2 - BS 5852

Cigarette - BS 5852 Match -


IMO MED FTP8 A652 - CAL

TB 117:2013


Maintenance:



Leather: Nature | Cat. C



Antracite \ C9X



Marrone \ C9Y



Testa di moro \ C9Z

Nature | Cat. C

Raw hide:

European bovine

Surface:

Aniline full grain

Thickness:

1,0 - 1,2 mm

Dry friction:

ISO 11640 > 50 cycles

Fire tests:

EN 1021-1/2 - BS 5852

Cigarette - BS 5852 Match -

CAL TB 117:2013 - NFPA

260/UFAC

Maintenance:



Characteristics and cleaning:

As guarantee of the quality and authenticity of our products, we advice that porosity, scars, grain differences on the surface of the leather coverings, are not to be considered defect, but characteristics of the animal's life.

To clean use a dry cloth. Any stains should be removed promptly with an absorbent cloth. Do not rub.