

76



Description

76 results from introducing a vacuum into a strata composed of hot white and clear glass with copper mesh between; the vacuum causes the white layer to pull away through the embedded mesh, leaving numerous tendrils of white glass suspended within an interstitial space as it goes.

76.1m requires remote mounted power supplies. Remote mounted power supplies recommended for ease of long term maintenance. Installation to be done by certified personnel to ensure code compliance.

Each pendant comes standard with 118"1/8 of coaxial cable.

Up-charge applies for lengths over 118"1/8. Cable length can be adjusted on site.

White, black or brushed nickel canopy.

Lamps and power supplies are included.

Lamp: 0.4W LED, 2700K, 70lm

Materials: Blown glass, copper mesh, braided metal coaxial cable, electrical components, steel canopy

Power Supply: Integral. Remote mounted for 76.1m.

Bocci recommends remote mounting power supplies for ease of long-term maintenance.

Environment: Indoor, dry location. IP30

76

Dimensions

76.1) $\varnothing 4\frac{5}{8}$ x $\frac{1}{4}$ "H canopy

76.1 deep) $\varnothing 4\frac{5}{8}$ x $1\frac{5}{8}$ H canopy

76.1m) $\varnothing 1\frac{1}{8}$ canopy

Pendant size: $\pm \varnothing 5\frac{7}{8}$

Standard Coaxial Cable Length:

- $118\frac{1}{8}$ "

Additional Coaxial Cable Lengths:

- $236\frac{1}{4}$ "
- $354\frac{3}{8}$ "
- $472\frac{3}{8}$ "
- $590\frac{1}{2}$ "
- $708\frac{5}{8}$ "
- $826\frac{3}{4}$ "
- $944\frac{7}{8}$ "
- 1063 "

Pendant



$\pm \varnothing 5\frac{7}{8}$

